

CURRENTS AND VOLTAGES

VALVE NO.		3	4a	4b	5a	5b	5c	5d	6	7a	7b	7c	7d	7	7 GRID	i _a TOTAL	V _a	i _{bias} RECT.	V _{bias} RECT.	i MAINS	V MAINS
CONDITION																					
STAND BY, HAILER	KEY OPEN	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	47	0,5	230
	KEY PRESSED W ₀ = 0	0	45	45	50	50	50	50	0	0	0	0	0	0	0	330	570	30	32	1,7	220
	KEY PRESSED W ₀ 50W	0	30	30	80	80	80	80	0	0	0	0	0	0	0	420	550	210	32	1,9	220
(A1) CW	KEY OPEN	0	0	0	0	0	0	0	0	0	0	0	0	0	0	100	580	25	42	0,8	220
	KEY PRESSED	0	0	0	0	0	0	0	45	90	90	90	90	360	15	545	550	190	33	2,3	220
(A2) MCW	KEY OPEN	0	0	0	0	0	0	0	0	0	0	0	0	0	0	100	580	25	41	0,8	220
	KEY PRESSED	6	35	35	70	70	70	70	43	85	85	85	85	340	15	870	530	190	32	3,2	220
(A3) SIMPLEX	KEY OPEN	0	0	0	0	0	0	0	0	0	0	0	0	0	0	100	580	25	41	0,8	220
	KEY PRESSED UNMODULATED	0	40	40	45	45	45	45	42	85	85	85	85	340	15	700	550	270	28	2,8	220
	KEY PRESSED MODULATED 90%	0	32	32	95	95	95	95	40	90	90	90	90	360	15	800	530	270	28	3,0	220
(A3) DUPLEX	KEY OPEN	0	30	30	27	27	27	27	41	90	90	90	90	360	15	700	550	10	42	2,8	220
	KEY PRESSED UNMODULATED	0	35	35	35	35	35	35	41	90	90	90	90	360	15	710	550	200	32	2,8	220
	KEY PRESSED MODULATED 90%	0	35	35	85	85	85	85	41	85	85	85	85	340	15	860	530	200	32	3,1	220
(A3) DUPLEX POWER 1/10	KEY PRESSED UNMODULATED	0	39	39	39	39	39	39	45	25	25	25	25	100	15	440	570	200	32	2,0	220
	KEY PRESSED MODULATED 90%	0	38	38	45	45	45	45	45	30	30	30	30	120	15	480	550	700	32	2,0	220
(A1) CW	KEY PRESSED ANTENNA DETUNED	0	0	0	0	0	0	0	46	32	32	32	32	128	15	290	570	190	34	1,2	220

GÆLDER FRA OG MED NR. 20

15. DEK. 1956

INGENIØRFIRMAET M. P. PEDERSEN KØBENHAVN				Skala	Tegn. NO 2
Tegn. af	Arkiv	Map.	Dato		
HB/EBS				MAY 1963	
NORMAL METER READINGS				A 199 CV	